

TES 70 Series *SmartCharge*

The TES 70 Series Smart Charge is a smart charging station that makes it easy to charge your EV fleets and make sure they are ready to go. Designed for commercial applications – workplace, multifamily, hospitality, and the public sector. Including built-in alerts and a smart dashboard to visualize detailed reports on electricity used, carbon offset fuel savings and more.



Fleet management capability enables fleet managers to:

- Easily configure custom fleet programs by individual vehicle and major vehicle type or both
- Track departure, return times, and energy delivered to each vehicle, and monitor charging fees for any of your public chargers.
- Schedule both start and stop of charging sessions to take advantage of off-peak and partial peak electricity rates.
- Receive alerts to notify exceptions in return times, energy delivered and departure times to maximize the daily success of the entire fleet. Generate a robust set of reports and analytics.
- Optional cable management system

Features

- Sleek, elegant design
- Compact form factor
- Commercial-grade aluminum body
- “At-a-Glance” LED status
- Rugged outdoor-rated enclosure
- Full warranty replacement policy available
- Easy to install and service

Smart Features

- Fleet vehicle management
- Fleet access control
- Fleet manager portal
- Late plug-in/plug-out alerts
- Schedule start time
- Session data and analytics
- State of health monitoring





TERRA

ENERGY SERVICES BY **ACDI**

Power Specs

| | |
|--|---|
| AC Power Output, maximum (per port) | Level II: 11.52 kW (240VAC@48A) or 9.984kW (208VAC@48A) |
| AC Power Input (per port) | Level II: 48A; Line 1, Line 2 and Earth (no neutral) |
| Ports Per Charging Station | Two |
| Vehicle to Charger Connection (per port) | SAE J1772 EV Connector, 18ft Cable |
| Energy Metering Accuracy | 1% at 15 min interval (standard), 0.5% optional |
| Standby Power (per port) | 3.46 W Typical |
| Service Panel Breaker (per port) | Dual-pole trip 60A breaker, dedicated circuit |

Safety Specs

| | |
|--|---|
| Safety, Ground Fault Circuit Interrupt | 20mA CCID with auto retry (every 15 seconds) |
| Automatic Plug-Out Detection | Pwr terminated per SAE J1772 spec: SMS/email |
| General Safety Compliance | UL 2231-1, 2231-2, UL2594 and NEC Article 625 |

Network Specs

| | |
|--------------------------------|-------------------------------|
| Data Communication Cellular | Cellular 4G LTE |
| Network Communication Protocol | TCP/IP |
| Network Security | HTTPS; 128-bit AES Encryption |

Communication Device Specs

| | |
|------------|---|
| LED Array | High visibility, multi-color visual status indication |
| LCD Screen | 4 line, 16 characters per line |

Environmental Specs

| | |
|-----------------------|--------------------------|
| Outdoor Rated | NEMA 3R per NEMA250-1997 |
| Operating Humidity | Up to 95% non-condensing |
| Operating Temperature | -30°C to 50°C ambient |

Other Specs

| | |
|------------------------------|-------------------------------|
| Surge Protection | 6kV@3,000A |
| EMI Compliance | FCC Part 15 Class A |
| Dimensions | 20.5" H x 7.4" W x 7.4" D |
| Approximate Shipping Weights | Device: 21 lbs. |
| | Pedestal mount: 12.5 lbs. |
| | Wall mount bracket: 11.5 lbs. |

For more information on Terra Energy Services and our products, please call 800.990.2234 or visit terraenergyservice.com

